

## PNEUMATIC CHAMBER LEAK TEST - CTE-GM



# PNEUMATIC CHAMBER LEAK TEST CTE-GM

**BIG MODEL** 

#### **FUNCTION**

With a **total visibility** and thanks to his plexiglass design, it is **very quick and easy** to see if there is a leak on the packaging.

#### **USE CASE:**

It is most often used in edge industries of production line for its simplicity and fully pneumatic operation and for his big capacity to control big series. It is very useful in case of quality crisis or during an audit to control a whole lot.

Most often used for vials or bottles, it is also used to remove air bubbles and impurities in the enamel, emulsion, or those present before brazing or welding.



#### **BENEFITS**

- Ergonomic with his opening on door
- Easy to use
- Reliable and economical
- Adapted to the production environment / Robust

- Test on receipt of raw materials, in production, before shipment

- Low maintenance

- Easy and quick maintenance due to the absence of electrical connection
- Long life thanks to its design



ACRN - Parc d'activités du Moulin d'Ecalles - 76750 BUCHY - France Tél. : +33 (0)2 32 80 81 40 - Fax : +33 (0)2 32 80 14 44 - www.acrn.fr - commercial@acrn.fr Capital de 173 000 € - Siret : 399 007 251 00024 - APE : 2620Z - RM : 399 007 251 - TVA : FR 55 399 007 251





#### **TECHNICAL INFORMATION**

Вох	Transparent PMMA box with front door opening
Range of measurement and accuracy	From -0.1 to -0.85 Bar as standard. Accuracy +/- 2%
Useful dimensions	Length (L) 500 x Depth (D) 450 x Height (H) 500 mm
Reading the depression	Needle pressure gauge 50 mbar resolution
Units	Bar, Psi
Air supply	<ul> <li>On compressed air network from</li> <li>6 to 8 bars connected to Rislan®</li> <li>8mm pipe. (not included)</li> </ul>
Weight	60 kg
Thickness	30 mm depending on the RDM study
Depression adjustment	regulator with filter
Depression time	Adjustable timing device from 0 to 999 s.
Principle of the test	Visual
Temperature	From 0 to 40°c
Standards	ASTM D4991, ASTM D5094, ASTM D4169, EN 14401, DIN55528 (Part 1, 2, 3, 4 , 5)

#### **OPTIONS**

Air drain valve for easy return to PA.
Support trolley for a better mobility
Adjustable timing device from 0 to 99,999 seconds
Needle vacuum gauge with a better resolution (see *)



#### **DELIVERED WITH:**

• A calibration certificate LNE/COFRAC





ACRN - Parc d'activités du Moulin d'Ecalles - 76750 BUCHY - France Tél. : +33 (0)2 32 80 81 40 - Fax : +33 (0)2 32 80 14 44 - www.acrn.fr - commercial@acrn.fr Capital de 173 000 € - Siret : 399 007 251 00024 - APE : 2620Z - RM : 399 007 251 - TVA : FR 55 399 007 251



### ACRN A GLOBAL OFFER for your packaging quality controls



#### Calibration and annual maintenance ACRN is equipped with a metrology laboratory.

Setting up tests, choice of materials, state of the art, work on repeatability we can advise you according to your needs (tecnology, budget, ergonomics).

> Leak testing and dynamometric testing Our skills and equipment for leak testing and dynamometric testing for packaging

#### Major manufacturers have trusted us for many years













ACRN - Parc d'activités du Moulin d'Ecalles - 76750 BUCHY - France Tél. : +33 (0)2 32 80 81 40 - Fax : +33 (0)2 32 80 14 44 - www.acrn.fr - commercial@acrn.fr Capital de 173 000 € - Siret : 399 007 251 00024 - APE : 2620Z - RM : 399 007 251 - TVA : FR 55 399 007 251