

DOYPACK, SACHET AND POUCH WELD TESTERS ECRASE DOYPACK ATS-XD



THE MODULAR ELECTRO-PNEUMATIC MODEL



DOYPACK, SACHET AND POUCH **WELD TESTERS** ECRASE DOYPACK **ATS-XD**

THE MODULAR ELECTRO-PNEUMATIC MODEL

FUNCTION

The ATS-xD allows to control the **weld strength of plastic** or metal packaging such as doypacks, doypack refills, pouches, sachets and tubes directly containing liquid or semi viscous product:









Doypack Recharge Doypack

Pochette Sachet

For an utilisation on the production line or in the laboratory. It can be used in addition to the ATS tube weld tester.

Why do you have to test your weld? During the heatsealing process, defects in the weld can appear due to the temperature of the electrodes and the presence of impurities. The implementation of a crush test allows to verify the integrity of the weld of your sample, and thus the absence of leakage or microleakage. This test is essential to validate the reliability of the weld.

ACRN, which has 20 years of experience in the field, will be able to advise you for these adjustments and recommend loads to be applied according to the type of packaging of your sample. ACRN will also provide you a table of the force exerted according to the pressure of the compressed air supply.

This is a **fast**, **simple** and totally **repeatable** test deployed by many packaging manufacturers.

TWO TESTS

The advantage of this product is that it can perform two different tests thanks to its digital interface in which the user can vary the pressure force and test duration.

- Test with micro-leak that grows with the pressure and causes a burst

- Burst test to determine the resistance of welds





The electro-pneumatic ATS-XD is suitable for doypacks, sachets, pouches and tubes of all kinds.





Porte résistante. ouverture sur 2 faces





BENEFITS

- Simple, fast, robust and fully repeatable testing

- Adapted to **production environments** thanks to innovative and intuitive design:

- **Perfected cleanability** thanks to its multi-opening door

- Magnetic pressers quickly interchangeable

according to the type of packaging

- Wide range of capacities from 10

kg to 3,300 kg in pressure force depending on the pneumatic cylinder

- Easy-to-use digital interface with **traceability of** results via printer or export software

- Precise location of the leak

- No maintenance required

- Specific housing on request for a **precise adjustment** of the positioning of your sample ensuring a very good **repeatability** of your measurement.

TECHNICAL INFORMATION

	U		
Crushing of doypacks	PVC doypacks crusher on rigid metal frame, unbreakable trans- parent polycarbonate door, painted mild steel support frame		
Air supply	compressed air from 0 to 10 bars		
Power supply	220-230 V / 50 – 60 Hertz		
Pressure adjustment	Pressure regulator		
Reading	Pressure gauge graduated from 0 to 10 bars		
Timer	Adjustable from 2 to 999 seconds at +/- 1 second		
Security	Emergency stop button/door switch		
Power supply connection	Connection to the compressed air network by means of a Rislan tube with an external diameter of 8 mm		
Digital output	RS232		
weight	65 kg		

OPTIONS









TECHNICAL SPECIFICATIONS ACCORDING TO THE SUPPORT FORCE

	ATS-XD 400	ATS-XD 2200	ATS-XD 3300
Force min	20 kg	400 kg	400 kg
Force max	400 kg	2 200 kg	3 300 kg
External dimensions	L 530 * D 400 * H 700 mm	L 400 * D 340 * H 580 mm	L 400 * D 340 * H 580 mm
Inside dimensions for sample	L 200 * D 270 mm	L 200 * D 270 mm	L 200 * D 270 mm
Weight	25 kg	65 kg	65 kg

DELIVERED WITH:

• A calibration certificate connected to LNE/COFRAC



ACRN A GLOBAL OFFER for your packaging quality controls



Calibration and annual maintenance ACRN is equipped with a metrology laboratory.

Setting up tests, choice of materials, state of the art, work on repeatability we can advise you according to your needs (tecnology, budget, ergonomics).

> Leak testing and dynamometric testing Our skills and equipment for leak testing and dynamometric testing for packaging

Major manufacturers have trusted us for many years





